DESIGNED TO **SIMPLIFY** LIFE ENGINEERED TO **MAGNIFY** RESULTS



AGROTRON L 720

For more information visit deutz-fahr.co.za of contact 0861 128 128

DEUTZ-FAHR SA (DF Africa (Pty) Ltd) is part of the Africom Group of Companies | africom.co



TECHNICAL DATA		AGROTRON L720
ENGINE		AOROTRON LIZO
Emissions		Tier 3
Manufacturer		TCD 2013 L106 2V DCR
Cylinders/Capacity	No./cm ³	6/7 146
Bore/Stroke	mm	108/130
Max. Power with DPC	kW/hp	162/220
Rated power (2 000/25EC)	kW/hp	145/197
Homologated power (2 000/25 EC)	kW/hp	157/214
Speed max. capacity	/min.	2 000 - 2 350
Max.Torque	Nm	836
ank capacity	litres	340
	illes	340
RANSMISSION		
Electronic powershift		•
chuttle reversing	l ()	•
Max. Speed	km/h	40
No. of gears (with creeper)		27/27
Brakes and Steering		
front axle central drive		•
Differential locks front/rear		•
lydraulic service brake	No.	•
teering angle	degrees	55°
All 4 wheels braking system		•
HYDRAULIC SYSTEM		
oad sensing system (closed centre)	rpm	•
Pump flow rate	litres/min.	113
OWERLIFT		
ifting force rear	kp	10 000
Remote control of rear powerlift		•
ront powerlift		0
P.I.O		
ront P.T.O. speed	rpm	0
Rear P.T.O. clutch oil immersed 540E - 1 000		•
Remote control on rear mudguard		•
CAB		
Noise level	dB(A)	74
Airconditioning		•
Pneumatic suspension		0
DIMENSIONS AND WEIGHTS		
Standard rear tyres		650/65R42
standard front tyres		540/65R34
Vheelbase Vheelbase	mm	2 985
ength	mm	4 800
Height	mm	3 020
Vidth	mm	2 550
Ground clearance	mm	600
otal unladen weight	kg	7 270
	"S	7.2.0