

FUNCTIONS



Back plate up : 0 - 75°



Back plate down : 0 - 22°



Trendelenburg position : 0 - 18°



Anti - trendelenburg position : 0 - 18°



Tilt left : 18°



Tilt right : 18°



Leg plate up / down : 10° / 90°
Head plate up/down: 50° / 90°



Leg plate horizontal extension : 90°



Longitudinal slide of tabletop : 15 cm



Longitudinal slide of tabletop : 15 cm



Minimum height : 71 cm



Maximum height : 111 cm

OPTIONS

GROUP 1 / ACCESSORY OPTIONS



A0




A1




A2



A3



A4



A5



A6

DESCRIPTION OF OPTION CODES

A0 WITHOUT ACCESSORIES

A1 CONTROL PANEL

A2 ARM BOARD

A3 LATERAL SUPPORT

A4 LEG CRUTCHES

A5 ANESTHESIA SCREEN FRAME

A6 RESTRAINT STRAP

Do not select the others if you select without accessory.
If you select the others you can select all or 1-2-3 ... of them.

GENERAL SPECIFICATIONS

- In order to attain a high degree of process security in the OR, every movement has to meet a virtually unlimited variety of possibilities for ideal patient positioning in all surgical disciplines, hard and durable stainless steel has to be selected, unique design for two kickout-pin oil cylinder on the base be used and forward-looking technology for stable oil flowing with precise controller undertaken, so that man and machinery could harmonize perfectly.
- Well-designed as well as fine closed steel column ensures hygiene and reduces the cost for cleaning, disinfection and rusty possibility.
- Gas spring activate head and leg plates .
- Special materials for tabletop pave the way for x-ray technology, compatible with interventional radiology.
- Connection with all kinds of accessories ensures different surgeries
- Provide longitudinal slide, guaranteeing effective use of interventional radiology during surgery, especially orthopedic operation.
- Foot-control pedal ensures tabletop's movement when power is off.

TECHNICAL SPECIFICATIONS

■ Length of tabletop	: 204 cm
■ Width of tabletop	: 52 cm
■ Safe Operating Load (Inc. Mattress and Accessories)	: 180 kg
■ Weight	: approx 150 kg
■ Volume	: 0,68 m ³
■ Fixation of table	: Mechanically

ELECTRICAL SPECIFICATIONS

■ Power Supply	: 110~240V 50~60Hz
■ Power	: 850VA

