FUNCTIONS



Backrest Adjustment: 0 - 45°

OPTIONS

GROUP 1 / IV STAND OPTIONS





DESCRIPTION OF OPTION CODES

WITHOUT OTHER ACCESSORIES



Must select only one of them.

STRETCHER

GENERAL SPECIFICATIONS

- Antibacterial and cleanable artificial leather covered, high density foam mattress.
- Backrest position is adjusted by gas spring between 0-65 degrees.
- Trendelenburg position is adjusted by gas spring between 0-12 degrees.
- Ergonomic, durable and easily cleanable metal rails system with maximum safety.
- Height adjustable IV stand is able to be located on both head and foot side corners.
- There are four bumpers on corners of bed for protection.
- Epoxy painted steel construction is, resistant to corrosion.
- Upper platform is portable in case of emergency, it can be easily removed and transferred from trollev.
- Oxygen tube holder.
- Moves easily by 150 mm diameter four castors, two of them with brake to fix the position.
- Optional vinlex color choice. (RVX)

TECHNICAL SPECIFICATIONS









FUNCTIONS



Backrest Adjustment: 0 - 65°



Trendelenburg position: 0 - 12°

OPTIONS

GROUP 1 / IV STAND OPTIONS





GROUP 2 / OTHER ACCESSORY OPTIONS



DESCRIPTION OF OPTION CODES

WITHOUT OTHER ACCESSORIES

V STAND : ONE HEIGHT ADJUSTMENT

RESTRAINT STRAP

Must select only one of them.

Do not select the others if you select without accessory.

If you select the others you can select all or 1-2-3 ... of them.

STRETCHER

GENERAL SPECIFICATIONS

- Antibacterial and cleanable artificial leather covered, high density foam mattress.
- Backrest position is adjusted by gas spring between 0-65 degrees.
- Trendelenburg position is adjusted by gas spring between 0-12 degrees.
 Ergonomic, durable and easily cleanable metal rails system with maximum safety.
- Height adjustable IV stand is able to be located on both head and foot side corners.
- There are four bumpers on corners of bed for protection.
- Epoxy painted steel construction is, resistant to corrosion.
- Upper platform is portable in case of emergency, it can be easily removed and
- Oxygen tube holder.
- Moves easily by 150 mm diameter four castors, two of them with brake to fix the position.
- Optional vinlex color choice. (RVX)

TECHNICAL SPECIFICATIONS

	Width	:	70,5 cm
	Length	:	211 cm
	Height	:	90 cm
	Weight	:	approx 58 kg
п	Volume		1 46 m ³







FUNCTIONS



Backrest Adjustment: 0 - 65°



Trendelenburg position: 0 - 12°



Mattress platform minimum height :



Mattress platform maximum height : 105 cm

STRETCHER EMERGENCY

GENERAL SPECIFICATIONS


- Antibacterial and cleanable artificial leather covered, high density foam mattress.
- Backrest position is adjusted by gas spring between 0-65 degrees by pulling black control handle located on foot.
- Trendelenburg position is adjusted by gas spring between 0-12 degrees by pulling black control handle located on foot.
- Height of stretcher is adjusted between 74- 105 cm by hydraulic pump.
- Ergonomic, durable and easily cleanable metal rails system with maximum safety.
- There are four bumpers on corners of bed for protection against to surrounding.
- Epoxy painted steel construction is, resistant to corrosion.
- There is an oxygen tube holder.
- Moves easily by 150 mm diameter castors.
- Optional vinlex color choice. (RVX)

TECHNICAL SPECIFICATIONS

■ Width	: 73,5 cm
■ Length	: 209 cm
■ Weight	: approx 102 kg
■ Volume	: 1,25 m ³

OPTIONS

GROUP 1 / CASTOR OPTIONS



GROUP 2 / IV STAND OPTIONS



GROUP 3 / OTHER ACCESSORY OPTIONS



DESCRIPTION OF OPTION CODES

- CASTOR TWO WITH BRAKE (150 MM)
- CASTOR CENTRAL & DIRECTIONAL LOCK (150 MM)
- WITHOUT OTHER ACCESSORIES
- V STAND : ONE HEIGHT ADJUSTMENT SYSTEM
- RESTRAINT STRAP
- Must select only one of them.
- Do not select the others if you select without accessory. If you select the others you can select all or 1-2-3 ... of them.





DOLSAN



FUNCTIONS



Backrest adjustment: 0 - 70°



Mattress platform minimum height :

68 cm

Anti - trendelenburg position : 0 - 12°



Mattress platform maximum height : 98 cm

STRETCHER EMERGENCY

GENERAL SPECIFICATIONS

- Water and heat resistant, compact laminate (HPL) bed platform with X-Ray feature
- Anti-bacterial, effaceable imitation leather coated high density sponge lying surface.
- Head side movement by the help of shock absorber mechanism.
- Hydraulic height movement, trendelenburg and reverse trendelenburg positions.
- Pedal system that can be controlled at both sides.
- Hygienic, easily cleanable lower frame hidden by ABS plastic.
- Oxygen tube holder.
- Ergonomic, durable and easily cleanable aluminum rails system with maximum safety.
- There are four bumpers on corners of bed for protection.
- Metal components dyed with anti-corrosion electrostatic powder paint after being treated with phosphate.
- Moves easily by 150 mm diameter castors.
- Optional vinlex color choice. (RVX)

TECHNICAL SPECIFICATIONS

	Width	:	71,5 cm
-	Length	:	221 cm
	Weight	:	approx 150 kg
	Volume	:	1,25 m ³

OPTIONS

GROUP 1 / CASTOR OPTIONS









GROUP 2 / IV STAND OPTIONS





GROUP 3 / OTHER ACCESSORY OPTIONS



DESCRIPTION OF OPTION CODES

- CASTOR TWO WITH BRAKE (150 MM)
- T12 CASTOR CENTRAL & DIRECTIONAL LOCK (150 MM)
- CASTOR CENTRAL & DIRECTIONAL LOCK (150 MM)
- WITHOUT OTHER ACCESSORIES
- WS IV STAND : ONE HEIGHT ADJUSTMENT SYSTEM
- RESTRAINT STRAP
- Must select only one of them.
- Do not select the others if you select without accessory. If you select the others you can select all or 1-2-3 ... of them.







DOLSAN



FUNCTIONS



Backrest adjustment: 0 - 70°



Trendelenburg position: 0 - 12°



Upper platform is able to be transferred from one trolley to other trolley.

STRETCHER TRANSPORT

GENERAL SPECIFICATIONS

- Antibacterial and cleanable artificial leather covered, high density foam mattress.
- Owing to resistant and useful rail system, upper platform is able to be transferred from one trolley to other trolley.
- Backrest position is adjusted by gas spring between 0-65 degrees by pulling black
- Trendelenburg position is adjusted by gas spring between 0-12 degrees by pulling black control handle.
- Ergonomic, durable and easily cleanable metal rails system with maximum safety.
- There are four bumpers on corners of bed for protection against to surrounding
- There is an oxygen tube holder.
- Epoxy painted steel construction is, resistant to corrosion.
- Moves easily by 150 mm diameter castors.
- Optional vinlex color choice. (RVX)

TECHNICAL SPECIFICATIONS

■ Width	: '	70,5 cm
■ Length (one trolley)	: :	213 cm
■ Length (two trolley)	: -	404,5 cm
■ Weight	: 6	approx 122 kg
■ Volume	: :	2,60 m ³

OPTIONS

GROUP 1 / CASTOR OPTIONS





GROUP 2 / IV STAND OPTIONS





GROUP 3 / OTHER ACCESSORY OPTIONS



DESCRIPTION OF OPTION CODES

- CASTOR TWO WITH BRAKE (150 MM)
- CASTOR CENTRAL & DIRECTIONAL LOCK (150 MM)
- WITHOUT OTHER ACCESSORIES
- V STAND : ONE HEIGHT ADJUSTMENT SYSTEM
- RESTRAINT STRAP
- Must select only one of them.
- Do not select the others if you select without accessory. If you select the others you can select all or 1-2-3 ... of them.









DOLSAN

